



Construction Products Regulation Declaration of Performance

1 DoP Reference Number

2 Product Description

3 Product Serial Number(s)

4 Intended use

5 Manufacturer

6 Authorised Representative

7 Assessment and verification of constancy of performance

8 Relevant Harmonised Standard

9 First year of CE Marking

10 Notified Body that performed Type Test

11 Type Test Report Reference No.

12 Essential Characteristics

1. Water-tightness - jointing of drainage channels

2. Load bearing capacity, deflection under load

- Maximum load

- Permanent set

3. Durability

13 Specific Technical Documentation (Article 37/38)

ED/E1/0166

ACO KerbDrain HB480 Channels Type M

Channels - 4923, 4926, 4934, 4935, 4936, 4937, 4943

Access Unit - 4927

Drop Kerb Units - 4931, 4932 Centre Stone Unit - 4933, 4983

Collection and conveyance of surface water from areas subject to pedestrian and/ or vehicular traffic

ACO Technologies plc

ACO Business Park, Hitchin Road, Shefford

Bedfordshire, SG17 5TE **United Kingdom**

Not Applicable

System 3

EN 1433: 2002

2008

1502

2/23.24/2010, 2/39.33/2009, 2/39.40/2009, 2/39.41/2009, 2/23.2/2010, 2/23.10/2010,

2/389.10/2011

Declared performance

No Leakage

D 400*

Flexural Strength ≥ 22 N/mm² Compressive Strength ≥ 90 N/mm²

*Maximum Load Class when installed according to D 400 installation details

Not Applicable

The performance of the product(s) identified in points 2 and 3 is in conformity with the declared performance in point 12. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 5.

Signed for and on behalf of the Manufacturer by

Richard Hill **Managing Director**

ACO Technologies PLC 20/05/2013